


AC1200 Wi-Fi Router **MU-MIMO** Gigabit

Full Gigabit | Dual Band









Faster Wi-Fi with MU-MIMO



Supports Smart Roaming

Highlights

oneMesh™ Flexibly Create a Whole-Home Wi-Fi

Create a Mesh network by connecting one or more OneMesh[™] range extenders to your Archer A6 for seamless whole-home coverage.



10× Faster Connectivity

One Gigabit WAN port and four Gigabit LAN ports deliver speeds up to 10× faster than standard Ethernet connections. Let every member of your family simultaneously enjoy high-speed network on their phones, tablets and laptops.[†]



(O)

Wi-Fi Dead-Zone Killer

Eliminate weak signal areas with Wi-Fi coverage for the whole house.

One Wi-Fi Name

Stay connected to the same network name in every room.

Smart Roaming

Enjoy uninterrupted streaming, surfing and more—even when moving around your home.




Unified Management

Manage the whole-home Wi-Fi by managing the central node via Tether app/Web UI.

Upgrade to Mesh Network



Enjoy Mesh network without having to replace your existing router by simply updating your OneMesh[™] router's firmware. Check full list of OneMesh[™] routers and range extenders at: https://www.tp-link.com/onemesh/a6/compatibility ***More compatible devices are coming soon**.



Highlights


Personalized Management

Block inappropriate content and set daily limits for the total time children/staff spend online through Parental Controls. Guest Network creates a separate access point for guests, to ensure your privacy is secure.



efficient.‡






MU-MIMO technology serves multiple devices at once, reducing wait time, increasing Wi-Fi throughput for every device, and making each stream more

Features





Speed

- Ultimate Wireless Speed 867 Mbps on 5 GHz + 300 Mbps on 2.4 GHz
- MU-MIMO Simultaneously transfer data to multiple devices for 2× faster
- Support 802.11 ac Provide a data transfer rate 3 times faster than 802.11n for each stream

Wi-Fi Range


 Ultimate Range Wi-Fi – Four external antennas deliver a Wi-Fi signal to every corner of your home, making all of your connections more efficient and stable



Reliability

- IPTV Support IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming
- Smart Connect Intelligently switches each device's connection to the optimum available Wi-Fi band
- Secure VPN Access Provide a private network with a safe and secure OpenVPN and PPTP VPN connection

Features



Easy Management

- Intuitive Web UI Ensures quick and simple Installation without hassle
- Hassle-free Management with Tether App Network management is made easy with the TP-Link Tether App, available on any Android and iOS device
- TP-Link ID Binds the router to your TP-Link ID and other family member's accounts to manage the router



Security

- Active Defense Protect your home network with firewalls and wireless encryption
 WPS –Makes secure wireless connection quick and easy with the push of a button
- Guest Network Provide separate access for guests while securing the home network
- Parental Controls Restricts internet access time and contents for children devices
- Access Control Establish a whitelist or blacklist to allow or block certain devices from accessing the internet


Ease of Use

- Wi-Fi Schedule The wireless network can be automatically off within a specified period when you do not need the wireless connection
- LED Control Automatically turns your router's LEDs off within a specified period

Specifications

Hardware

- Ethernet Ports: 1× 10/100/1000 Mbps WAN Port, 4×10/100/1000 Mbps LAN Port
- Buttons: WPS/Wi-Fi Button, Power On/Off Button, Reset Button
- Antennas: 4 Fixed Omni Directional Antennas
- External Power Supply: 12V/1A
- Dimensions (W x D x H): $8.5 \times 4.6 \times 1.2$ in ($215 \times 117 \times 32$ mm)



Wireless

- Frequency: 2.4 GHz and 5 GHz
- Transmit Power: FCC:<30dBm(2.4 GHz & 5 GHz)
- · Reception Sensitivity: 5 GHz:
- 11a 6Mbps:-93dBm; 11a 54Mbps:-78dBm;
- 11ac HT80 mcs9:-62dBm; 2.4 GHz:
- 11g 54Mbps:-78dBm;
- 11n HT20 mcs7:-74dBm;
- 11n HT40 mcs7:-71d

• Wireless: 867 Mbps on 5 GHz + 300 Mbps on 2.4 GHz

```
CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz)
```

```
11ac HT20 mcs8:-69dBm;11ac HT40 mcs9:-65dBm;
```

· Wireless Function: Enable/Disable Wireless Radio, WMM · Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

Specifications

Software

- · Quality of Service: Device Prioritization
- · WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
- Management: Access Control, Local Management, Remote Management
- DHCP: Server, DHCP Client List, Address Reservation
- Port Forwarding: Port Forwarding, Port Triggering, UPnP, DMZ
- Dynamic DNS: DynDns, NO-IP, TP-Link
- Access Control: Parental Controls, Local Management Control, White List, Black List
- Firewall Security: SPI Firewall, IP and MAC Address Binding
- · Protocols: IPv4, IPv6
- · Guest Network: 2.4 GHz Guest Network, 5 GHz Guest Network

Others

- · Certification:
- CE, FCC, RoHS
- System Requirements: NetWare, UNIX or Linux
- Java-enabled browser
- Cable or DSL Modem
- Environment:
- Package Contents Wireless Router Archer A6
- Power Adapter
- **RJ45 Ethernet Cable**
- Quick Installation Guide



For more information, please visit https://www.tp-link.com/products/details/Archer-A6.html

or scan the QR code left

Attention: This device may only be used indoors in all EU member states and EFTA countries.

Specifications are subject to change without notice. TP-Link is a registered trademarks of TP-Link Technologies Co., Ltd. All rights reserved. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. [†]Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and will vary as a result of network conditions, client limitations, and environmental factors, including materials, obstacles, volume and density of traffic, and client location.

[‡]Use of MU-MIMO requires clients to also support MU-MIMO.

Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS,

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other

Subscription with an internet service provider (for internet access)

Operating Temperature: 0°C~40°C (32°F ~104°F)

Operating Humidity: 10%~90% non-condensing