Advanced Power Protection

APC Back-UPS BX Series 750VA - 2200VA



APC™ Back-UPS™ BX series is a cost effective power protection solution for home and home office environments.

The series comprehensive VA range with premium features further enables single UPS capabilities

Home Entertainment

Living room essentials

Ideal Power Protection for the following environments and devices:



Home Office

Work from home & remote learning devices

Modem / Router

APC

- PC Desktop Computer
- PC Monitor
- Network-attached Storage



- TV Box
- Television
- Music Speaker



Smart Home

IoT electronics

- Modem / Router
- Smart Speaker
- Home Security /
 - Surveillance Camera


www.apc.com





Protect your devices from power surges and outages

? How does a UPS protect my uptime?



Battery backup is key to home continuity

The electronic devices you rely on for communication, security and entertainment depend on a stable network connection,

Ensure reliable uptime and clean power for your critical devices.

Comprehensive Power Capacity Range



Models ranging from 750VA-2200VA; choose a solution aligned with your specific application and runtime needs

Form Factor:

Compact for office and business spaces (*BX750MI-MS: 160 x 120 x 355 mm*).

Outlets

3-5 battery backup with surge protection outlets

Functional ease-of-use

Front panel LED green lights to easily tell the functional status

Visibility and Manageability Software



In the event of an extended power outage, prevent potential data loss or corruption with PowerChute Personal Edition Software

1Gb Network Protection

Safeguards your equipment and valuable files from "back door" surges traveling along data lines without sacrificing internet speed

Automatic Voltage Regulation (AVR)

Life Is Or

Instantly corrects incoming utility power without utilizing the battery, saving the battery for when it is needed most



APC Back-UPS technical specifications BX Series



	BX750MI-MS	BX950MI-MS	BX1200MI-MS	BX1600MI-MS	BX2200MI-MS	
Output						
Power Rating	750VA/410W	950VA/520W	1200VA/650W	1600VA900W	2200VA/1200W	
Nominal Output Voltage	230V					
Output Voltage (On Battery)	230+/-10%@ 100% load					
Output Frequency (Hz)	50/60HZ +/-0.5Hz					
Тороlоду	Line Interactive					
Waveform Type	Stepped approximation to a sinewave					
Output Connections (Battery Backup)	2 Universal + 1 IEC 320 C13) 2 Universal + 2 IEC 320 C13	4 Universal + 1 IEC 320 C13	4 Universal	4 Universal	
Input						
Nominal Input Voltage	230V					
Input Connections	NEMA 5-15P					
Input Cord	1.2 m					
Input frequency	50 Hz or 60 Hz					
USB Charging	No					
Batteries & runtime						
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte :					
Typical Backup Time at ½ Load	8.5 min	6.5 min	5 min	6.5 min	8.5 min	
Typical Backup Time at Full Load	1 min	1 min	1 min	1 min	1 min	
Typical Recharge Time	6 hours	6-8 hours	8 hours	8 hours	8 hours	
Communications & Manag	ement					
LED Indicators	Visual LED indicators					
Data Line Protection	RJ 45 Gigabit					
Interface Ports	273					
Software	PowerChute Personal Edition					
Physical	-					
Dimensions (HxWxD) mm	160 x 7	20 x 355		190 x 140 x 390		
Weight (kg)	5.4	6.1	7.6	10.3	12.3	
Environmental						
Operating Environment	0 - 40 °C					
Operating Relative Humidity	0 - 95 %					
Operating Elevation	0-3000 meters					
Storage Temperature	15 - 40 °C					
Storage Relative Humidity	0-95%					
Conformance	•					
Approvals	CB Meet EN62040-1 / CE / IEC-62040-1 / IEC-62040-2					
Standard Warranty	2 years repair or replace					
RoHS Compliant	Yes					

