

Choose the Multi-Function Centre that suits your needs

Inkjet Multi-Function Centre Series

brother  
at your side




**DCP-T300**

- Print / Scan / Copy
- Print speed: Up to 11ipm (mono) and 6ipm (colour)\*
- Print resolution: Up to 1,200 x 6,000 dpi
- Paper tray: Up to 100 sheets
- 1-Line LCD




**DCP-T500W**

- Print / Scan / Copy
- Print speed: Up to 11ipm (mono) and 6ipm (colour)\*
- Print resolution: Up to 1,200 x 6,000 dpi
- Paper tray: Up to 100 sheets
- Wireless LAN
- Mobile printing
- 1-Line LCD



**DCP-T700W**

- Print / Scan / Copy
- Print speed: Up to 11ipm (mono) and 6ipm (colour)\*
- Print resolution: Up to 1,200 x 6,000 dpi
- Automatic document feeder: Up to 20 sheets
- Paper tray: Up to 100 sheets
- Wireless LAN
- Mobile printing
- 1-Line LCD



**MFC-T800W**

- Print / Scan / Copy / Fax
- Print speed: Up to 11ipm (mono) and 6ipm (colour)\*
- Print resolution: Up to 1,200 x 6,000 dpi
- Automatic document feeder: Up to 20 sheets
- Paper tray: Up to 100 sheets
- Wireless LAN
- Mobile printing
- 1-Line LCD



brother  
at your side

Smarter Design.  
Bigger Savings.

BLACK  
**6000**  
page-yield\*



MFC-T800W



Refill Tank System



www.brother.com



One-stop centre for free downloadable templates



Brother strongly recommends the use of genuine Brother consumable products only. Benefits include better quality print, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please note that your machine warranty may not cover any damages arising from the use of non-genuine consumables.

Microsoft, Windows, the Windows logo and/or other Microsoft products referenced herein are either registered trademarks of Microsoft Corporation in the U.S. and/or other countries. Brother and its logo are trademarks of Brother Industries Ltd., Japan. All specifications are subject to change without notice. All registered trademarks referenced herein are the property of their respective companies. Brother International Corporation, Japan.

\* Based on ISO/IEC 24734. For more information, please refer to www.brother.com/rd/printspeed  
\* Two black ink bottles included in box are applicable to MFC-T800W, DCP-T700W and DCP-T500W only.



Designed to give you big savings, the new Brother Inkjet Multi-Function Centre series features new Refill Tank System and offers ink bottles with ultra-high 6000 page-yield<sup>#</sup>. You can now maximise your savings and benefit from a smarter design that makes ink refilling effortless!

## Refilling is so easy with **Refill Tank System** 3 Easy Steps!



**Open cover.**

Accessing ink tank is so easy with the cover right in front.



**Refill ink tank.**

Remove tank cap. Tilt ink bottle at 45° angle and gently squeeze it to refill ink tank.



**You're done!**

Replace cap and close cover. It's that easy!

## Exceedingly Affordable

Save more with Brother's low cost ink that provides up to 6,000 page-yield<sup>#</sup>. Now, high print volume users can reduce overall operating costs with every printout.

Moreover, with Brother's original refill ink, you minimise the risk of print head damage. This means less repair and replacement costs on your machine.

Make the most out of your budget and choose Brother's original refill ink. Maximise savings day after day!



<sup>#</sup> Refers to black ink. Colour ink: 5000 page-yield. Quoted approx. yields are extrapolated based on Brother original methodology using Test Patterns ISO/IEC 24712. Quoted approx. yields are not based on ISO/IEC 24711.

## User-Friendly Refill Experience

Most conventional printers require users to tilt the ink bottles vertically when refilling, which increases risk of spillage. Brother's smart design allows for refilling at an optimised 45° refilling angle. This minimises ink leakage and takes the hassle out of refilling.



### Other Printers



Potential spillage

### Brother's Smart Design



Minimise spillage

## Saves Space and Convenient

Other printers with external ink tanks usually require additional room for opening and closing of the ink tank compartment, as well as for reviewing ink levels.

Brother's Refill Tank System features a smart design with an embedded, front-access ink tank and a see-through cover. This saves space effectively and makes it easy to check how much ink is left.




### Other Printers



Wastes space

### Brother's Smart Design



Saves space

	DCP-T300	DCP-T500W	DCP-T700W	MFC-T800W
Functions	Print, Scan, Copy	Print, Scan, Copy, Wireless Network, Mobile Print	Print, Scan, Copy, Wireless Network, Mobile Print, Automatic Document Feeder	Print, Scan, Copy, Fax, Wireless Network, Mobile Print, Automatic Document Feeder
<b>GENERAL</b>				
Memory	64MB			
Display	1-Line			
Interface	Hi-Speed USB 2.0			
Wireless Network	-			
<b>COLOUR PRINTER</b>				
Print Speed (Laser Comparable) <sup>^</sup>	Up to 11ipm (mono) and 6ipm (colour)			
Print Speed (Fast Mode)	Up to 27ppm (mono) and 10ppm (colour)			
Print Resolution	Up to 1,200 x 6,000 dpi			
Borderless Printing	Yes: A4, LTR, A6, Photo (102 x 152mm / 4" x 6"), Indexcard (127 x 203mm / 5" x 8"), Photo-2L (127 x 178mm / 5"x7")			
Ink Save Mode	Yes			
Mobile Print	-			
Brother iPrint&Scan, Google Cloud Print™				
<b>COLOUR COPY FUNCTION</b>				
Copy Speed (Laser Comparable) <sup>^^</sup>	-			
Copy Resolution	Print: Max. 1200 x 2400 dpi Scan: Max. 1200 x 1200 dpi			
N in 1 Copy	Yes (Including ID Card Copy)			
Base Colour Removal	Yes			
<b>COLOUR SCAN FUNCTION</b>				
Scan Resolution	Optical: Up to 1,200 x 2,400 dpi Interpolated: Up to 19,200 x 19,200 dpi (For XP / Vista / Windows 7 / Windows 8)			
"Scan To" Feature	Image, Email, File			Image, Optical Character Recognition, Email, File
<b>MONO FAX FUNCTION</b>				
Modem	-			14.4 kbps
Memory Transmission <sup>***</sup>	-			Up to 170 pages
Speed Dials	-			40
Group Dials	-			Up to 6 groups
Out of Paper Reception <sup>***</sup>	-			Up to 170 pages
PC-Fax	-			5 ending & Receiving* (USB only)
<b>ADDITIONAL FEATURES</b>				
Poster Print / Copy	Yes			
Enlargement / Reduction Ratio	25% - 400% in 1% increments			
<b>PAPER HANDLING</b>				
Paper Input (Standard Tray)	Up to 100 sheets			
Paper Output	Up to 50 sheets			
Automatic Document Feeder	-			Up to 20 sheets
Paper Handling Sizes (Standard Tray)	A4, LTR, LGL, EXE, A5, A6, Photo (102 x 152mm / 4" x 6"), Indexcard (127 x 203mm / 5" x 8"), Photo-2L (127 x 178mm / 5" x 7"), C5 Envelope, Com-10, DL Envelope, Monarch (LGL is only for Philippines, Thailand, Malaysia, Vietnam, Gulf, Indonesia, India)			
Media Type	Plain, Inkjet, Glossy			
<b>SUPPORTED OS AND SOFTWARE</b>				
Supported Operating Systems	Windows: XP / XP x64 / Vista / 7 / 8 / 8.1 Mac: OS X v10.7.5/v10.8.x/v10.9.x	Windows: XP / XP x64 / Vista / 7 / 8 / 8.1 Server 2003 / Server 2003 R2 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 Mac: OS X v10.7.5 / v10.8.x / v10.9.x		
Network Management Tools	-			
BRAdmin Professional 3*, Driver Deployment Wizard*, BRAdmin Light**				
<b>SUPPLIES</b>				
Ink Bottles	Ultra High Yield (Black) BT6000 BK: Approximate Yield 6000 A4 pages**. Ultra High Yield (Colour) BT5000 C/M/Y: Approximate Yield 5000 A4 pages**			
Brother Paper	BP71GA: A4 glossy photo paper BP71GP20: 4" x 6" glossy photo paper BP60MA: A4 matte paper BP60PA: A4 plain paper			
<b>DIMENSIONS &amp; WEIGHT</b>				
Without Carton	435mm (W) x 374mm (D) x 161mm (H), 7.1kg		435mm (W) x 374mm (D) x 180mm (H), 8.3kg	

<sup>^</sup> Based on ISO/IEC 24734. For more information, please refer to [www.brother.com/rd/printspeed](http://www.brother.com/rd/printspeed)

<sup>^^</sup> Based on ISO/IEC 24735 for models with Automatic Document Feeder. For more information, please refer to [www.brother.com/rd/printspeed](http://www.brother.com/rd/printspeed)

\* Not supported on Mac and Linux. Available for download at <http://support.brother.com>

\*\* Not supported on Linux. Available for download at <http://support.brother.com>

\*\*\* Receiving is for Windows® only

\*\*\*\* Approximate yields are extrapolated based on Brother original methodology using Test Patterns ISO/IEC 24712. Approximate yields are not based on ISO/IEC 24711.

\*\*\*\*\* Based on ITU-T Test Chart No 1/MMF