



Timeless classic

Customized stable firmware for storage safety

No need to wait while creating

Large storage for creative work

Built-in high-rate LDPC ECC functionality

UNLEASH CREATIVITY

Specially designed for creators, the T-CREATE CLASSIC SATA SSD adopts a traditional appearance while featuring a highly reliable SMI Controller with customized stable firmware and a well-chosen 3D TLC flash. It offers ultra-fast read/write speeds of 550/520 MB per second. With a classic design and incredible performance, it provides creators with stable, high-speed user experience.

CLASSIC SATA III SSD



Specification

Interface	SATA III 6Gb/s
Capacity	1TB ^[1]
Color	SILVER
Voltage	DC +5V
Operation Temperature	0°C ~ 70°C
Terabyte Written Performance	1TB : 800TB ^[2]
Performance	ATTO / Crystal Disk Mark: 1TB Read 550MB/s ; Write 520MB/s ^[3] IOPS: 1TB 4K Random Read/Write: 70K/60K IOPS max ^[3]
Dimensions	100(L) x 69.9(W) x 7(H)mm
Operating System	Windows 10 / 8.1 / 8 / 7, MAC OS 10.4 or later, Linux 2.6.33 or later
Humidity	0°C ~ 55°C / 5% ~ 95% RH, non-condensing
Vibration	20G (non-operating)
Shock	1500G
MTBF	1,000,000 hours
Warranty	3-year limited warranty

Ordering Information

Color	Capacity	Team P/N
SILVER	1TB	T253TA001T3C601

[1] 1GB=1,000,000,000 Bytes. In OS system, it would be displayed as 1,000,000,000 Bytes/1024/1024/1024 = 0.93GB

[2] Definition and conditions of TBW (Terabytes Written) are based on JEDEC standard

[3] Transmission speed will vary according to different hardware/software conditions, therefore the data can only be used for basic reference.

※We reserve the right to modify product specifications without prior notice.